


COLLECTION | originals



Our *originals* collection encapsulates the rustic and aged charm of a truly authentic antique wooden floor. These floors are made to order using modern materials and construction methods to meet the most demanding building specifications.

Available in wide boards and parquet, this range rich coloured flooring is specifically suited to historic buildings or warehouse conversions, but can equally serve as a statement floor in any modern setting.

The grain is enhanced by both surface planing and soft brushing, adding to the authenticity of these aged floors. Loved by designers and architectural specialists these create a striking look suitable for both heritage and contemporary interiors. Available in two thicknesses of engineered boards in plank, herringbone or chevron.

A selection of swatches – more colours available



WIDEPLANK

COLOURS	WIDTH x LENGTH	GRADES	CONSTRUCTION/PROFILE
Abbey Ale, Barrel	140mm x 1800 -3000mm	Rustic Mix (A/B)	16mm thickness: 12mm first class birch plywood with 4mm oak top layer.
Brown, Beautiful	180mm	Rustic A	
Blonde, Brown Stout,	220mm	Rustic 1-Bis	21mm thickness: 15mm first class birch plywood with 6mm oak top layer.
Lovely Lager, Mr	260mm	Prime/Select	
Barley, Ms Stout,	280mm		
Oaked White, Silly	300mm plus On request		Tongue and groove four sides, micro-level 4 sides
Seasons, Smoked			
Porter, Smokey Ale,			
Smokey Sessions			

HERRINGBONE & CHEVRON

As wideplank above	90 x 450mm 120 x 600mm 140 x 700mm 180 x 900mm	As above	As above
--------------------	---	----------	----------

AVAILABLE GRADES:

- PRIME/SELECT - Grain is a variation of straight grain and medullary rays on boards which are flat sawn. Occasional healthy pin knots up to max 10mm. Colour fairly uniform. No cracks or sapwood allowed.
- 1-BIS - Grain is straight with natural grain variation allowed. Flat Sawn. Healthy sound knots, (filled) allowed up to 25mm. • Black knots allowed up to 20mm
- RUSTIC A - Natural wood colour differences with filled healthy knots up to a maximum of 35mm. No end cracks or sapwood allowed.
- RUSTIC – Natural wood colour differences with filled healthy knots up to a maximum of 45mm. No end cracks or sapwood allowed. 50% mix of each of both grades two grades (Natural/Rustic, Select/Natural, etc

For more detailed information on grading please see our document *Grading Explained* at www.vanspeijck.co.uk/library

FINISHES

This unique collection is created using a combination of techniques which include reactive stains, bleach and coloured oils. Each board is finished with three coats of a specially developed oxidative hybrid oil. For maintenance information see www.vanspeijck.co.uk/library/

INSTALLATION RECOMMENDATIONS

All Van Speijck floors will benefit from installation by a skilled flooring specialist. We recommend installation using the full stick-down method. Please see our guide for more detailed instructions on installation and subfloor preparation Our clients expect nothing less than the high standards we demand from our installers. Learn more on our website at www.vanspeijck.co.uk/library/

ENVIRONMENTALLY FRIENDLY FLOORS

We pride ourselves on working in close collaboration with timber mills which source raw materials from forests with genuinely strong eco credentials and who only manufacture floorboards using ecological and sustainable production methods. The majority of our timber collections are FSC[®] certified or PEFC chain of custody standard. We believe that our partners' on-going investment and commitment to innovate will benefit us all and we are proud to be actively supporting their businesses. Learn more on our website at www.vanspeijck.co.uk/sustainability

